

SAFETY DATA SHEET

Aka-Lube Clear WF

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Trade name Aka-Lube Clear WF Product no. 49101015-49101017 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture Lubricant for metallographic polishing Uses advised against No special 1.3. Details of the supplier of the safety data sheet Company and address Akasel A/S Svogerslev Hovedgade 48 4000 Roskilde Denmark +45 57 84 05 01 www.akasel.com E-mail safety@akasel.com SDS date 27-09-2021 SDS Version 1.0 1.4. Emergency telephone number Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures". **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Not classified according to Regulation (EC) No. 1272/2008 (CLP) 2.2. Label elements Hazard pictogram(s) Not applicable Signal word Not applicable Hazard statement(s)

Not applicable Safety statement(s) General

> -Prevention

Response



Storage

-

Disposal

Hazardous substances No special 2.3. Other hazards Additional labelling Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Propane-1,2-diol	CAS No.: 57-55-6	40-60%		
	EC No.: 200-338-0			
	REACH: 01-2119456809-23- xxxx			
	Index No.:			
Polyethylene glycol	CAS No.: 25322-68-3	40-60%		
	EC No.: 500-038-2			
	REACH:			
	Index No.:			

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

No special

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) and continue until irritation stops.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice



immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

No special

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

No special

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2).

5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

No special conditions required.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Room temperature 18 to 23°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)



This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propane-1,2-diol Long term exposure limit (8 hours) (ppm): 150(total) Long term exposure limit (8 hours) (mg/m³): 474(total)/10(particulates)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

Product/substance	Propane-1,2-diol
DNEL	168mg/m3
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	Propane-1,2-diol
DNEL	10mg/m3
Route of exposure	Inhalation
Duration	Long term – Local effects - Workers
Product/substance	Propane-1,2-diol
DNEL	213mg/kg bw/dg
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population
Product/substance	Propane-1,2-diol
DNEL	50mg/m3
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population
Product/substance	Propane-1,2-diol
DNEL	85 mg/m3
Route of exposure	Oral
Duration	Long term – Systemic effects - General population
Product/substance	Propane-1,2-diol
DNEL	10mg/m3
Route of exposure	Inhalation
Duration	Long term – Local effects - General population
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 260 mg/l Freshwater
Product/substance	Propane-1,2-diol
PNEC	26mg/l
Route of exposure	Marine water

PNEC



Duration of Exposure	
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 183mg/l Intermittent release
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 572 mg/kg d.w Freshwater sediment
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 50mg/kg d.w Soil
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 2000mg/l Activated Sludge Plant
Product/substance PNEC Route of exposure Duration of Exposure	Propane-1,2-diol 57.2mg/kg d.w Marine water sediment

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis. General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

Wash hands after use.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

No specific requirements

Hand protection



Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	-	EN374-2	11/2/

Eye protection

Work situation	Туре	Standards	
At risk of splashing in the eyes	Wear safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Liquid

Colour

Clear

Odour

None

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product. pH

Testing not relevant or not possible due to nature of the product. Density (g/cm³)

Testing not relevant or not possible due to nature of the product. Viscosity

Testing not relevant or not possible due to nature of the product. Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product. Boiling point (°C)

Testing not relevant or not possible due to nature of the product. Vapour pressure

Testing not relevant or not possible due to nature of the product. Vapour density

Testing not relevant or not possible due to nature of the product. Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product. Evaporation rate (n-butylacetate = 100)

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to nature of the product. Ignition (°C)

Testing not relevant or not possible due to nature of the product. Auto flammability (°C)

Testing not relevant or not possible due to nature of the product. Explosion limits ((v v/v))

Testing not relevant or not possible due to nature of the product. Explosive properties

Testing not relevant or not possible due to nature of the product. Oxidizing properties

Testing not relevant or not possible due to nature of the product.



Solubility Solubility in water Testing not relevant or not possible due to nature of the product. n-octanol/water coefficient Testing not relevant or not possible due to nature of the product. Solubility in fat (g/L) Testing not relevant or not possible due to nature of the product. 9.2. Other information
SECTION 10: Stability and reactivity
 10.1. Reactivity No data available 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions No special 10.4. Conditions to avoid No special 10.5. Incompatible materials Strong acids, strong bases, strong oxidizing agents, and strong reducing agents. 10.6. Hazardous decomposition products The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Acute toxicity

Product/substance Test method Species Route of exposure Test Result Other information	Propane-1,2-diol Rabbit Dermal LD50 >2000 mg/kg		
Product/substance Test method Species Route of exposure Test Result Other information	Propane-1,2-diol Guinea pig Intraperitoneal LD50 9718 mg/kg		
Product/substance Test method Species Route of exposure Test Result Other information	Propane-1,2-diol Rat Oral LD50 6423 mg/kg		
Product/substance	Propane-1,2-diol		



Test method		
Species	Rabbit	
Route of exposure	Oral	
Test	LD50	
Result	18500 mg/kg	
Other information		
Product/substance	Propane-1,2-diol	
Test method		
Species	Rabbit	
Route of exposure	Inhalation	
Test	LC50 (2 hours)	
Result	>317 mg/L	
Other information	5	
Serious eye damage/irr Based on available d Respiratory sensitisation Based on available d Skin sensitisation Based on available d Germ cell mutagenicity Based on available d Carcinogenicity Based on available d	ata, the classification criteria are not met. tation ata, the classification criteria are not met.	
STOT-single exposure Based on available d STOT-repeated exposur Based on available d Aspiration hazard	ata, the classification criteria are not met. ata, the classification criteria are not met. e ata, the classification criteria are not met. ata, the classification criteria are not met.	

12.1. Toxicity

Product/substance	Propane-1,2-diol
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	EC50
Result	110 mg/L
Other information	

Product/substance Propane-1,2-diol



Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	710 mg/L
Other information	
Product/substance	Propane-1,2-diol
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	ErC50

12.2. Persistence and degradability

Other information

Result

Product/substance	Propane-1,2-diol
Biodegradable	Yes
Test method	OECD 301 F
Result	81,7 %

19000 mg/L

12.3. Bioaccumulative potential

Product/substance	Propane-1,2-diol
Test method	
Potential	No
bioaccumulation	
LogPow	-0,7800
BCF	0.09
Other information	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

EWC code

Not applicable

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information



14.1 - 14.4 Not dangerous goods according to ADR, IATA and IMDG. ADR/RID Not applicable IMDG Not applicable "MARINE POLLUTANT" No IATA Not applicable 14.5. Environmental hazards Not applicable 14.6. Special precautions for user Not applicable 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

Sources

Regulation (EU) No 1357/2014 of 18 December 2014 on waste. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on

classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CE = Conformité Européenne CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement

EWC = European Weste Catalogue



GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer (IARC) IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit. SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Additional information Not applicable The safety data sheet is validated by iro@akasel.com

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en